



C1008

60# Natural Kraft | snappLock | 40#

This is an unbleached, brown kraft facestock. It has excellent strength and tear resistance. This natural kraft facestock is most commonly used in high end prime labeling, but it also works well as a corrugated coverup label.

Since this facestock has a high level of stiffness, we recommend testing on curved surfaces to prevent edge lift.

Features and Benefits

- ✦ for products needing a natural, high end appearance
- ✦ strong strength and tear resistance

caliper (+/- 10%) 4.7mil
 CD tensile (lbs/in) 48/26
 MD tear (g) 130/147

facestock



an aggressive hot-melt adhesive
for difficult to label surfaces

SnappLock features high initial tack and peel values. It has excellent die cutting capabilities, maximizing press speeds. SnappLock excels on cylindrical applications and smooth, or moderately textured surfaces.

Common Applications

- ✦ powder coated
- ✦ stainless steel
- ✦ low surface energy plastics
- ✦ recycled corrugated

caliper (+/- 10%) 1mil
 min application temp (°F) 40
 service range (°F) -40-190
 180° peel (PLI) 7.2
 RT loop tack (PLI) 11.3
 saft (°F) 160

adhesive

This is a 40# bleached, super calendered kraft liner. This liner features excellent die cutting and matrix stripping.

caliper (+/- 10%) 2.4mil

liner

total caliper (+/- 10%) 8.1mil

this product has a 1 year shelf life when stored at 72°F and 50% relative humidity

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty