

C10232.3mil Gloss Wht PP TC | ap1 | 40#

This is a white, high gloss, BOPP film that is top-coated for flexographic, gravure, silkscreen, and letterpress processes. Features include high opacity, excellent hot/cold moisture resistance, semi-squeeze performance, high stiffness for conversion and automatic dispensing, balanced biaxial orientation for superior, even die cutting enhancing label edge appearance and prolonging die life.

caliper (+/- 10%) 2.3mil opacity % 80 MD/CD elongation % 85/110 MD/CD tensile (K lbs/in) 26.1/21.7

-- 1: - - - (1 100/)



an aggressive hot-melt adhesive for difficult to label surfaces

Ap1 is a general-purpose adhesive that works well over a wide temperature range. Ap1 provides excellent die cutting and stripping.

			C	aliper (+/- 10%)	u.8mii
	Common Applications		min application temp (°F)		10
#	corrugated	井 low surface energy plas	tics se	rvice range (°F)	-40-140
#	packaging surfaces	high surface energy plas	stics	180° peel (PLI)	4.9
			RT	loop tack (PLI)	9.2
				saft (°F)	150

This is a 40# bleached, super calendered kraft liner. This liner features excellent die cutting and matrix stripping.

caliper (+/- 10%) 2.4mil

total caliper (+/- 10%) 5.5mil

this product has a 1 year shelf life when stored at 72°F and 50% relative humidity

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty