

## **C1025**3.4mil Wht Vinyl PT | hp1 | 50#

This is a white, semi-rigid, opaque, cadmium-free polymeric vinyl face stock. It is specifically formulated for use in the label and decal sign market. This product has excellent surface quality, printability, and product consistency. Testing ink and printing methods is recommended for use with this face stock.

caliper (+/- 10%) 3.4mil MD/CD elongation % 65/120 MD/CD tensile (lbs/in) 2.8/2.5



## an aggressive hot-melt adhesive for difficult to label surfaces

Hp1 is designed to hold strong in severe environments- with exposure to petroleum based oils, grease, organic solvents, and high humidity. Hp1 has very high peel and shear properties for use on durable applications.

		caliper (+/- 10%)	1mil
Common Applications mir		min application temp (°F)	45
HDPE	井 low surface energy plast	ics service range (°F)	-40-220
powder coated	smooth steel	180° peel (PLI)	8.2
		RT loop tack (PLI)	10.5
		saft (°F)	195

This is a 50# bleached, super calendered kraft liner. This liner features excellent die cutting and matrix stripping.

caliper (+/- 10%) 3.1mil

total caliper (+/- 10%) 7.5mil

this product has a 1 year shelf life when stored at 72°F and 50% relative humidity

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty