



C1036

50# Coated TT Opaque | crocLock HCW | 40#

This facestock is designed for pressure sensitive thermal transfer applications with conventional pre-print. The coatings on this grade are optimized for thermal transfer printing, while providing a surface for flexographic preprinting. This grade features a smooth surface and high strength for fast printing and matrix stripping. This facestock is coated with an opaque black barrier.

Features and Benefits

✦ black coated opaque barrier	caliper (+/- 10%)	3.1mil
✦ coatings designed for thermal transfer printing	smoothness (5S, PPS)	2.00
✦ smooth surface for good bar code reproduction	brightness %	85
✦ smudge resistance for durable bar code image	CD tensile (lbs/in)	17
✦ high strength for fast matrix stripping	MD tear (g)	42

facestock



an aggressive hot-melt adhesive
for difficult to label surfaces

the MVP at PRI Plus

CrocLock is designed with quick tack properties and excellent on press convertibility.

Common Applications

✦ wood	✦ plastics	caliper (+/- 10%)	1mil
✦ corrugated	✦ textured	min application temp (°F)	30
		service range (°F)	-40-145
		180° peel (PLI)	5.5
		RT loop tack (PLI)	6
		saft (°F)	140

adhesive

This is a 40# bleached, super calendered kraft liner. This liner features excellent die cutting and matrix stripping.

caliper (+/- 10%) 2.4mil

liner

total caliper (+/- 10%) 6.5mil

this product has a 1 year shelf life when stored at 72°F and 50% relative humidity

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty

www.priplus.com