



C1038L

1.5mil Clear PET | snappLock | 40#

This Clear Polyester film stock is designed for a wide variety of label applications. This film has been corona treated to enhance printability across many printing processes. It provides excellent tear strength, heat resistance, dimensional stability, and chemical resistance.

facestock

caliper (+/- 10%) 1.5mil



an aggressive hot-melt adhesive
for difficult to label surfaces

SnappLock features high initial tack and peel values. It has excellent die cutting capabilities, maximizing press speeds. SnappLock excels on cylindrical applications and smooth, or moderately textured surfaces.

adhesive

Common Applications

- ⚡ powder coated
- ⚡ stainless steel
- ⚡ low surface energy plastics
- ⚡ recycled corrugated

caliper (+/- 10%)	1mil
min application temp (°F)	40
service range (°F)	-40-190
180° peel (PLI)	7.2
RT loop tack (PLI)	11.3
saft (°F)	160

This is a 40# bleached, super calendered kraft liner. This liner features excellent die cutting and matrix stripping.

liner

caliper (+/- 10%) 2.4mil

total caliper (+/- 10%) 4.9mil

this product has a 1 year shelf life when stored at 72°F and 50% relative humidity

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty