



Dry Edge
series

Product Data Sheet

Rev. No. 02.05.01
Date 21DEC22

C1051 13" Dry Edge

50# Coated TT | crocLock HCW Dry Edge | 40#

This is a premium coated thermal transfer face sheet. A matte print receptive coating is specifically designed for excellent thermal transfer printability.

facestock

caliper (+/- 10%) 3.1mil



2-Sided Limited Ooze or 4-Sided No Ooze Dry Edge

an aggressive hot-melt adhesive

for difficult to label surfaces

the MVP at Pri Plus

CrocLock is designed with quick tack properties and excellent on press convertibility.

Common Applications

- ✦ wood
- ✦ corrugated
- ✦ plastics
- ✦ textured

caliper (+/- 10%)	1.2mil
min application temp (°F)	30
service range (°F)	-40-145
180° peel (PLI)	5.5
RT loop tack (PLI)	6
saft (°F)	140

adhesive

This is a 40# bleached, super calendered kraft liner. This liner features excellent die cutting and matrix stripping.

caliper (+/- 10%) 2.4mil

liner

total caliper (+/- 10%) 6.7mil

this product has a 1 year shelf life when stored at 72°F and 50% relative humidity

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty

www.priplus.com

PRI Plus | 608 Rye Beach Rd | Huron, OH 44839 | +1 800.813.8907