# Facestock



# C1055 13" Dry Edge

## 3mil Matte Wht PP TT | snappLock HCW Dry Edge | 40#

This is a white, miner-filled, BOPP film designed for applications requiring strength and durability. A mette print receptive coating is specifically designed for excellent thermal transfer printability.

> caliper (+/- 10%) 3mil



### 2-Sided Limited Ooze or 4-Sided No Ooze Dry Edge

an aggressive hot-melt adhesive for difficult to label surfaces

SnappLock features high initial tack and peel values. It has excellent die cutting capabilities, maximizing press speeds. SnappLock excels on cylindrical applications and smooth, or moderately textured surfaces.

		caliper (+/- 10%)	1.4mil
Common Applications		min application temp (°F)	40
powder coated    powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder coated   powder	🕂 low surface energy plast	ics service range (°F)	-40-190
stainless steel	recycled corrugated	180° peel (PLI)	7.2
		RT loop tack (PLI)	11.3
		saft (°F)	160

This is a 40# bleached, super calendered kraft liner. This liner features excellent die cutting and matrix stripping.

> caliper (+/- 10%) 2.4mil

6.8mil total caliper (+/- 10%)

this product has a 1 year shelf life when stored at 72°F and 50% relative humidity

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty