



C1060

Direct Thermal TC | crocLock | 40#

This facestock is a topcoated, medium sensitivity, direct thermal label designed for use in standard speed printers. Direct thermal provides good environmental resistance and high bar code scan rates.

Features and Benefits

- ✚ print speeds up to 8ips
- ✚ good chemical and environmental resistance
- ✚ scuff resistant
- ✚ suitable for rotated bar codes
- ✚ 190 sensitivity

| | |
|------------------------|--------|
| caliper (+/- 10%) | 3.1mil |
| brightness % | 77 |
| MD/CD tensile (lbs/in) | 35/17 |
| MD/CD tear (g) | 45/45 |

facestock



an aggressive hot-melt adhesive
for difficult to label surfaces

the MVP at PRI Plus

CrocLock is designed with quick tack properties and excellent on press convertibility.

Common Applications

- ✚ wood
- ✚ plastics
- ✚ corrugated
- ✚ textured

| | |
|---------------------------|---------|
| caliper (+/- 10%) | 1mil |
| min application temp (°F) | 30 |
| service range (°F) | -40-145 |
| 180° peel (PLI) | 5.5 |
| RT loop tack (PLI) | 6 |
| saft (°F) | 140 |

adhesive

This is a 40# bleached, super calendered kraft liner. This liner features excellent die cutting and matrix stripping.

| | |
|-------------------|--------|
| caliper (+/- 10%) | 2.4mil |
|-------------------|--------|

liner

total caliper (+/- 10%) 6.5mil

this product has a 1 year shelf life when stored at 72°F and 50% relative humidity

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty

www.priplus.com