



# C1061

## 2mil Silver VOID PET TC | snappLock | 50#

This bright silver polyester face stock is top-coated for flexographic, thermal transfer, and UV letterpress printing. It has a pattern release layer designed to indicate tampering when removed from various substrates.

facestock

|                          |       |
|--------------------------|-------|
| caliper (+/- 10%)        | 2mil  |
| MD/CD tensile (k lbs/in) | 26/35 |



an aggressive hot-melt adhesive  
for difficult to label surfaces

SnappLock features high initial tack and peel values. It has excellent die cutting capabilities, maximizing press speeds. SnappLock excels on cylindrical applications and smooth, or moderately textured surfaces.

adhesive

### Common Applications

- ✦ powder coated
- ✦ stainless steel
- ✦ low surface energy plastics
- ✦ recycled corrugated

|                           |         |
|---------------------------|---------|
| caliper (+/- 10%)         | 1mil    |
| min application temp (°F) | 40      |
| service range (°F)        | -40-190 |
| 180° peel (PLI)           | 7.2     |
| RT loop tack (PLI)        | 11.3    |
| saft (°F)                 | 160     |

This is a 50# bleached, super calendered kraft liner. This liner features excellent die cutting and matrix stripping.

liner

|                   |        |
|-------------------|--------|
| caliper (+/- 10%) | 3.1mil |
|-------------------|--------|

total caliper (+/- 10%) 6.1mil

this product has a 1 year shelf life when stored at 72°F and 50% relative humidity

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty