



C1076

8mil Wht Synthetic TT | ap1 | 50#

This matte finish, white opaque, mineral-reinforced polypropylene has excellent thermal transfer printability. It has an excellent combination of strength, rigidity, and yield. It is an excellent candidate for a wide range of applications where durability, strength, moisture, chemical resistance, and superior printability is required.

facestock

caliper (+/- 10%)	8mil
yield (lbs/in ²)	3066
MD/CD elongation %	500
MD/CD tensile (k lbs/in)	3/2
MD/CD tear (kg)	3/5.5



an aggressive hot-melt adhesive
for difficult to label surfaces

Ap1 is a general-purpose adhesive that works well over a wide temperature range. Ap1 provides excellent die cutting and stripping.

adhesive

Common Applications

- ✦ corrugated
- ✦ packaging surfaces
- ✦ low surface energy plastics
- ✦ high surface energy plastics

caliper (+/- 10%)	0.8mil
min application temp (°F)	10
service range (°F)	-40-140
180° peel (PLI)	4.9
RT loop tack (PLI)	9.2
saft (°F)	150

This is a 50# bleached, super calendered kraft liner. This liner features excellent die cutting and matrix stripping.

liner

caliper (+/- 10%)	3.1mil
-------------------	--------

total caliper (+/- 10%) 11.9mil

this product has a 1 year shelf life when stored at 72°F and 50% relative humidity

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty