



C1090

2mil Clear PP TC | snappLock | 4.6mil LF

This is a transparent, top-coated, BOPP film.

facestock

| | |
|--|--------|
| caliper (+/- 10%) | 2mil |
| surface tension | 42 |
| MD/CD elongation % | 180/55 |
| MD/CD tensile (k lbs/in ²) | 20/35 |



an aggressive hot-melt adhesive
for difficult to label surfaces

SnappLock features high initial tack and peel values. It has excellent die cutting capabilities, maximizing press speeds. SnappLock excels on cylindrical applications and smooth, or moderately textured surfaces.

adhesive

Common Applications

- ✦ powder coated
- ✦ stainless steel
- ✦ low surface energy plastics
- ✦ recycled corrugated

| | |
|---------------------------|---------|
| caliper (+/- 10%) | 1mil |
| min application temp (°F) | 40 |
| service range (°F) | -40-190 |
| 180° peel (PLI) | 7.2 |
| RT loop tack (PLI) | 11.3 |
| saft (°F) | 160 |

This is a 77# silicone liner, coated for easy release. This liner features excellent lay flat properties.

liner

| | |
|-------------------|--------|
| caliper (+/- 10%) | 4.6mil |
|-------------------|--------|

total caliper (+/- 10%) 7.6mil

this product has a 1 year shelf life when stored at 72°F and 50% relative humidity

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty