



# C1098

## Direct Thermal TC | timberTack+ | 40#

This facestock is a topcoated, medium sensitivity, direct thermal label designed for use in standard speed printers. Direct thermal provides good environmental resistance and high bar code scan rates.

### Features and Benefits

- ✦ print speeds up to 8ips
- ✦ good chemical and environmental resistance
- ✦ scuff resistant
- ✦ suitable for rotated bar codes
- ✦ 190 sensitivity

caliper (+/- 10%)	3.1mil
brightness %	77
MD/CD tensile (lbs/in)	35/17
MD/CD tear (g)	45/45

facestock



### an aggressive hot-melt adhesive for difficult to label surfaces

TimberTack is designed as a soft adhesive to create maximum contact with the application surface. TimberTack is an extra aggressive adhesive.

### Common Applications

- ✦ wood
- ✦ carpet backing
- ✦ livestock
- ✦ burlap
- ✦ HDPE
- ✦ recycled corrugated packaging

caliper (+/- 10%)	2mil
min application temp (°F)	10
service range (°F)	-60-145
180° peel (PLI)	5
RT loop tack (PLI)	6
soft (°F)	160

adhesive

This is a 40# bleached, super calendered kraft liner. This liner features excellent die cutting and matrix stripping.

caliper (+/- 10%)	2.4mil
-------------------	--------

liner

total caliper (+/- 10%) 7.5mil

this product has a 1 year shelf life when stored at 72°F and 50% relative humidity

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty