



# C1103

## 3.2mil Matte Wht Synthetic | snappLock B | 40#

This polyolefin-based, clay-coated film is designed to be compatible with most print methods. It provides superior performance where resistance to tear, grease, moisture, and temperature fluctuation is needed. This film will die cut and fold easily. It is compatible with hot stamping and embossing. Outdoor durability will last up to 18 months depending on the climate and exposure. When using for hand applied applications it is recommended to remove the liner from the label in order to reduce pickers curl.

facestock

caliper (+/- 10%) 3.2mil



an aggressive hot-melt adhesive  
for difficult to label surfaces

SnappLock features high initial tack and peel values. It has excellent die cutting capabilities, maximizing press speeds. SnappLock excels on cylindrical applications and smooth, or moderately textured surfaces.

adhesive

### Common Applications

- ⚡ powder coated
- ⚡ stainless steel
- ⚡ low surface energy plastics
- ⚡ recycled corrugated

caliper (+/- 10%)	1.5mil
min application temp (°F)	40
service range (°F)	-40-190
180° peel (PLI)	7.2
RT loop tack (PLI)	11.3
saft (°F)	160

This is a 40# bleached, super calendered kraft liner. This liner features excellent die cutting and matrix stripping.

liner

caliper (+/- 10%) 2.4mil

total caliper (+/- 10%) 7.1mil

this product has a 1 year shelf life when stored at 72°F and 50% relative humidity

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty