



C1113

50# Coated TT | frzBite | 40#

This facestock is designed for pressure sensitive thermal transfer applications with conventional pre-print. The coatings on this grade are optimized for thermal transfer printing, while providing a surface for flexographic preprinting. This grade features a smooth surface and high strength for fast printing and matrix stripping.

### Features and Benefits

✦ coatings designed for thermal transfer printing	caliper (+/- 10%)	3.1mil
✦ smooth surface for good bar code reproduction	smoothness (5S, PPS)	2.00
✦ smudge resistance for durable bar code image	opacity %	87
✦ high strength for fast matrix stripping	brightness %	85
✦ high brightness and blue-white shade for good label appearance	CD tensile (lbs/in)	17
	MD tear (g)	42

facestock



### an aggressive hot-melt adhesive for difficult to label surfaces

FrzBite is designed to perform well in cold temperature environments. FrzBite can withstand a level of condensation at low temperatures and excels in many food packaging applications.

### Common Applications

✦ plastics	✦ wood	caliper (+/- 10%)	1.5mil
✦ corrugated	✦ textured	min application temp (°F)	-10
		service range (°F)	-40-140
		180° peel (PLI)	5.9
		RT loop tack (PLI)	5.6
		saft (°F)	150

adhesive

This is a 40# bleached, super calendered kraft liner. This liner features excellent die cutting and matrix stripping.

caliper (+/- 10%) 2.4mil

liner

total caliper (+/- 10%) 7mil

this product has a 1 year shelf life when stored at 72°F and 50% relative humidity

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty

[www.priplus.com](http://www.priplus.com)