



C1115

2mil Wht PET TC | snappLock B+ | 50#

This white polyester film has a glossy high performance print receptive topcoat. This film provides excellent tear strength, heat resistance, dimensional stability, opacity, and chemical resistance. The high performance print surface is designed to enhance printability with a variety of printing processes- including flexographic and thermal transfer printing.

facestock

caliper (+/- 10%) 2mil



an aggressive hot-melt adhesive
for difficult to label surfaces

SnappLock features high initial tack and peel values. It has excellent die cutting capabilities, maximizing press speeds. SnappLock excels on cylindrical applications and smooth, or moderately textured surfaces.

adhesive

Common Applications

- ⚡ powder coated
- ⚡ stainless steel
- ⚡ low surface energy plastics
- ⚡ recycled corrugated

caliper (+/- 10%)	1.8mil
min application temp (°F)	40
service range (°F)	-40-190
180° peel (PLI)	7.2
RT loop tack (PLI)	11.3
saft (°F)	160

*Conforms to the composition requirements of Indirect Food Additive Regulation 21 CFR 175.105

This is a 50# bleached, super calendered kraft liner. This liner features excellent die cutting and matrix stripping.

liner

caliper (+/- 10%) 3.1mil

total caliper (+/- 10%) 6.9mil

this product has a 1 year shelf life when stored at 72°F and 50% relative humidity

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty