



# C1117 13" Dry Edge

## 3.2mil Matte Wht PE | timberTack C Dry Edge | 40#

This polyolefin-based, clay coated film is designed to be compatible with most print methods. This product provides superior performance where resistance to tear, grease, moisture, and temperature fluctuation is needed. This polyolefin will die cut and fold easily as well as being compatible with hot stamping and embossing. Outdoor durability will last up to 18 months depending on the climate and exposure. When using for hand applied applications it is recommended to remove the liner from the label in order to reduce pickers curl.

facestock

caliper (+/- 10%) 3.2mil

### 2-Sided Limited Ooze or 4-Sided No Ooze Dry Edge

an aggressive hot-melt adhesive  
for difficult to label surfaces

TimberTack is designed as a soft adhesive to create maximum contact with the application surface. TimberTack is an extra aggressive adhesive.

adhesive



### Common Applications

- ⚡ wood
- ⚡ carpet backing
- ⚡ livestock
- ⚡ burlap
- ⚡ HDPE
- ⚡ recycled corrugated packaging

caliper (+/- 10%)	2.2mil
min application temp (°F)	10
service range (°F)	-60-145
180° peel (PLI)	5
RT loop tack (PLI)	6
soft (°F)	160

This is a 40# bleached, super calendered kraft liner. This liner features excellent die cutting and matrix stripping.

liner

caliper (+/- 10%) 2.4mil

total caliper (+/- 10%) 7.8mil

this product has a 1 year shelf life when stored at 72°F and 50% relative humidity

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty