



C1119

2.6mil Gloss Wht PP TC | tire PC | 50#

This is a white, high gloss, BOPP film that is top-coated for excellent print performance and ink adhesion. It is print receptive for UV flexo, water flexo, gravure, UV inkjet, hot stamp, and thermal transfer printing methods.

Features and Benefits

- ✦ excellent die-cut performance
- ✦ pearlized look for graphics enhancement
- ✦ great stiffness for efficient dispensability

| | |
|--------------------------|---------|
| caliper (+/- 10%) | 2.6mil |
| gloss (45°) | 90 |
| Opacity % | 90 |
| MD/CD elongation % | 150/50 |
| MD/CD tensile (K lbs/in) | 13.1/29 |

facestock



an aggressive hot-melt adhesive
for difficult to label surfaces

Tire is designed to maintain adherence on rough surfaces.
Tire has excellent initial tack and flow.

This product has a Pattern Coating

Common Applications

- ✦ tires
- ✦ fabric
- ✦ recycled corrugated packaging

| | |
|---------------------------|---------|
| caliper (+/- 10%) | 1.4mil |
| min application temp (°F) | 10 |
| service range (°F) | -60—145 |
| 180° peel (PLI) | 5 |
| RT loop tack (PLI) | 6 |
| saft (°F) | 160 |

adhesive

This is a 50# bleached, super calendered kraft liner. This liner features excellent die cutting and matrix stripping.

| | |
|-------------------|--------|
| caliper (+/- 10%) | 3.1mil |
|-------------------|--------|

liner

total caliper (+/- 10%) 7.1mil

this product has a 1 year shelf life when stored at 72°F and 50% relative humidity

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty