



C1126

Direct Thermal TC | frzBite | 40#

This facestock is a topcoated, medium sensitivity, direct thermal label designed for use in standard speed printers. Direct thermal provides good environmental resistance and high bar code scan rates.

Features and Benefits

- ✦ print speeds up to 8ips
- ✦ good chemical and environmental resistance
- ✦ scuff resistant
- ✦ suitable for rotated bar codes
- ✦ 190 sensitivity

caliper (+/- 10%)	3.1mil
brightness %	77
MD/CD tensile (lbs/in)	35/17
MD/CD tear (g)	45/45

facestock



an aggressive hot-melt adhesive
for difficult to label surfaces

FrzBite is designed to perform well in cold temperature environments. FrzBite can withstand a level of condensation at low temperatures and excels in many food packaging applications.

Common Applications

- ✦ plastics
- ✦ wood
- ✦ corrugated
- ✦ textured

caliper (+/- 10%)	1mil
min application temp (°F)	-10
service range (°F)	-40-140
180° peel (PLI)	5.9
RT loop tack (PLI)	5.6
saft (°F)	150

adhesive

This is a 40# bleached, super calendered kraft liner. This liner features excellent die cutting and matrix stripping.

caliper (+/- 10%)	2.4mil
-------------------	--------

liner

total caliper (+/- 10%) 6.5mil

this product has a 1 year shelf life when stored at 72°F and 50% relative humidity

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty

www.priplus.com