



C1140

7.5mil Durable PE | timberTack HCW | 4.6mil

This white blown HDPE film is designed to print both sides via flexographic and thermal transfer print methods. This dDurable film has excellent UV and weather resistance, high tear strength, and can be used in cold temperature applications.

facestock

caliper (+/- 10%)	7.5mil
elongation %	1200
MD/CD tensile (k lbs/in)	4.5/4.2



an aggressive hot-melt adhesive
for difficult to label surfaces

TimberTack is designed as a soft adhesive to create maximum contact with the application surface. TimberTack is an extra aggressive adhesive.

adhesive

Common Applications

- ✦ wood
- ✦ carpet backing
- ✦ livestock
- ✦ burlap
- ✦ HDPE
- ✦ recycled corrugated packaging

caliper (+/- 10%)	1.5mil
min application temp (°F)	10
service range (°F)	-60-145
180° peel (PLI)	5
RT loop tack (PLI)	6
saft (°F)	160

This is a 77# silicone liner, coated for easy release. This liner features excellent lay flat properties.

liner

caliper (+/- 10%)	4.6mil
-------------------	--------

total caliper (+/- 10%) 13.6mil

this product has a 1 year shelf life when stored at 72°F and 50% relative humidity

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty