

**C1143****3.4mil Wht Vinyl PT | hp1 3mil | 50#**

This is a white, semi-rigid, opaque, cadmium-free polymeric vinyl face stock. It is specifically formulated for use in the label and decal sign market. This product has excellent surface quality, printability, and product consistency. Testing ink and printing methods is recommended for use with this face stock.

facestock

caliper (+/- 10%) 3.4mil
MD/CD elongation % 65/120
MD/CD tensile (lbs/in) 2.8/2.5



an aggressive hot-melt adhesive
for difficult to label surfaces

Hp1 is designed to hold strong in severe environments- with exposure to petroleum based oils, grease, organic solvents, and high humidity. Hp1 has very high peel and shear properties for use on durable applications.

adhesive

Common Applications

✦ HDPE
✦ powder coated

✦ low surface energy plastics
✦ smooth steel

caliper (+/- 10%) 3mil
min application temp (°F) 45
service range (°F) -40-220
180° peel (PLI) 8.2
RT loop tack (PLI) 10.5
saft (°F) 195

This is a 50# bleached, super calendered kraft liner. This liner features excellent die cutting and matrix stripping.

liner

caliper (+/- 10%) 3.1mil

total caliper (+/- 10%) 9.5mil

this product has a 1 year shelf life when stored at 72°F and 50% relative humidity

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty

www.priplus.com