



C1162

7mil Matte Wht PE | snappLock | 50#

This polyolefin-based, clay-coated film is designed to be compatible with most print methods. This film provides superior performance where resistance to tear, grease, moisture, and temperature fluctuation is needed. It will die cut and fold easily. It is also compatible with hot stamping and embossing. Outdoor durability will last up to 18 months depending on the climate and exposure. When using for hand held applications, it is recommended to remove the liner from the label in order to reduce pickers curl.

facestock

caliper (+/- 10%) 7mil



an aggressive hot-melt adhesive
for difficult to label surfaces

SnappLock features high initial tack and peel values. It has excellent die cutting capabilities, maximizing press speeds. SnappLock excels on cylindrical applications and smooth, or moderately textured surfaces.

adhesive

Common Applications

- ✦ powder coated
- ✦ stainless steel
- ✦ low surface energy plastics
- ✦ recycled corrugated

caliper (+/- 10%)	1mil
min application temp (°F)	40
service range (°F)	-40-190
180° peel (PLI)	7.2
RT loop tack (PLI)	11.3
saft (°F)	160

This is a 50# bleached, super calendered kraft liner. This liner features excellent die cutting and matrix stripping.

caliper (+/- 10%) 3.1mil

liner

total caliper (+/- 10%) 11.1mil

this product has a 1 year shelf life when stored at 72°F and 50% relative humidity

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty