

**C1164****2mil Matte Wht PET LSR PB | hp1 | 1.5PET | hp1+ | 50#**

This matte white polyester face stock has a laser printable top-coat. It has excellent tear strength, heat resistance, opacity, dimensional stability, and chemical resistance.

facestock

caliper (+/- 10%) 2mil



an aggressive hot-melt adhesive
for difficult to label surfaces

Hp1 is designed to hold strong in severe environments- with exposure to petroleum based oils, grease, organic solvents, and high humidity. Hp1 has very high peel and shear properties for use on durable applications.

Common Applications

✦ HDPE
✦ powder coated

✦ smooth steel
✦ low surface energy plastics

1st layer caliper (+/- 10%)	0.8mil
2nd layer caliper (+/- 10%)	1.8mil
min application temp (°F)	45
max service temp (°F)	-40-220
180° peel (PLI)	8.2
RT loop tack (PLI)	10.5
saft (°F)	195

adhesive

This is a 1.5mil Polyester liner. This PET liner is designed to offer excellent die cutting and label dispensing.

caliper (+/- 10%)	1.4mil
CD tensile (lbs/in)	23,000

This is a 50# bleached, super calendered kraft liner. This liner features excellent die cutting and matrix stripping.

caliper (+/- 10%)	3.1mil
-------------------	--------

liner

total caliper (+/- 10%) 9.1mil

this product has a 1 year shelf life when stored at 72°F and 50% relative humidity

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty

www.priplus.com