



# C1174

## 60# Saturated Litho w/Barrier | tire | 40#

This facestock is a saturated litho paper. It is coated for flexographic printing. Saturated litho has good weather resistance and conforms well to uneven surfaces. This facestock is laminated with a 0.5mil PET barrier for improved durability and strength.

facestock

### Features and Benefits

- ✦ compatible with both inkjet and laser printing
- ✦ dries quickly to help prevent smudge
- ✦ matte coating for subtle finish
- ✦ provides weather resistance
- ✦ conforms well to uneven surfaces
- ✦ impregnated paper for enhanced durability

caliper (+/- 10%)	4mil
MD/CD tensile (lbs/in)	25/17
MD/CD tear (g)	55/58



an aggressive hot-melt adhesive  
for difficult to label surfaces

Tire is designed to maintain adherence on rough surfaces.  
Tire has excellent initial tack and flow.

adhesive

### Common Applications

- ✦ tires
- ✦ fabric
- ✦ recycled corrugated packaging

caliper (+/- 10%)	1.8mil
min application temp (°F)	10
service range (°F)	-60-145
180° peel (PLI)	5
RT loop tack (PLI)	6
saft (°F)	160

This is a 40# bleached, super calendered kraft liner. This liner features excellent die cutting and matrix stripping.

liner

caliper (+/- 10%)	2.4mil
-------------------	--------

total caliper (+/- 10%) 8.2mil

this product has a 1 year shelf life when stored at 72°F and 50% relative humidity

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty