



# C1177

## 3.2mil Matte Wht PE | timberTack+ | 4.6mil

This polyolefin-based, clay-coated film is designed to be compatible with most print methods. This film provides superior performance where resistance to tear, grease, moisture, and temperature fluctuation is needed. It will die cut and fold easily. It is also compatible with hot stamping and embossing. Outdoor durability will last up to 18 months depending on the climate and exposure. When using for hand held applications, it is recommended to remove the liner from the label in order to reduce pickers curl.

facestock

caliper (+/- 10%) 3.2mil



an aggressive hot-melt adhesive  
for difficult to label surfaces

TimberTack is designed as a soft adhesive to create maximum contact with the application surface. TimberTack is an extra aggressive adhesive.

adhesive

### Common Applications

- ⚡ wood
- ⚡ carpet backing
- ⚡ livestock
- ⚡ burlap
- ⚡ HDPE
- ⚡ recycled corrugated packaging

caliper (+/- 10%)	1.8mil
min application temp (°F)	10
service range (°F)	-60-145
180° peel (PLI)	5
RT loop tack (PLI)	6
soft (°F)	160

This is a 77# silicone liner, coated for easy release. This liner features excellent lay flat properties.

liner

caliper (+/- 10%) 4.6mil

total caliper (+/- 10%) 9.6mil

this product has a 1 year shelf life when stored at 72°F and 50% relative humidity

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty