

C1184 60# Saturated Litho | hp1 | 50#

This facestock is a saturated litho paper. It is coated for flexographic printing. Saturated litho has good weather resistance and conforms well to uneven surfaces.

Features and Benefits

- + compatable with both inkjet and laser printing
- # dries quickly to help prevent smudge
- # matte coating for subtle finish
- # provides weather resistance
- # conforms well to uneven surfaces
- # impregnated paper for enhanced durability

caliper (+/- 10%)

MD/CD tensile (lbs/in)

3.2mil

25/17

MD/CD tear (q) 55/58



an aggressive hot-melt adhesive for difficult to label surfaces

Hp1 is designed to hold strong in severe environments- with exposure to petroleum based oils, grease, organic solvents, and high humidity. Hp1 has very high peel and shear properties for use on durable applications.

		caliper (+/- 10%)	1mil
Common Applications		min application temp (°F)	45
	井 low surface energy plast	ics service range (°F)	-40-220
powder coated		180° peel (PLI)	8.2
		RT loop tack (PLI)	10.5
		saft (°F)	195

This is a 50# bleached, super calendered kraft liner. This liner features excellent die cutting and matrix stripping.

> caliper (+/- 10%) 3.1mil

7.3mil total caliper (+/- 10%)

this product has a 1 year shelf life when stored at 72°F and 50% relative humidity

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty