

## **C1187**3.8mil Matte Wht PE | hp1 | 50#

This polyolefin-based, clay-coated film is designed to be compatible with most print methods. This film provides superior performance where resistance to tear, grease, moisture, and temperature fluctuation is needed. It will die cut and fold easily. It is also compatible with hot stamping and embossing. Outdoor duribility will last up to 18 months depending on the climate and exposure. When using for hand held applications, it is recommended to remove the liner from the label in order to reduce pickers curl.

caliper (+/- 10%) 3.8mil



## an aggressive hot-melt adhesive for difficult to label surfaces

Hp1 is designed to hold strong in severe environments- with exposure to petroleum based oils, grease, organic solvents, and high humidity. Hp1 has very high peel and shear properties for use on durable applications.

caliper (+/- 10%) 1.2mil Common Applications min application temp (°F) 45 # HDPE # low surface energy plastics service range (°F) -40-220 # powder coated # smooth steel 180° peel (PLI) 8.2 RT loop tack (PLI) 10.5 saft (°F) 195

This is a 50# bleached, super calendered kraft liner. This liner features excellent die cutting and matrix stripping.

caliper (+/- 10%) 3.1mil

total caliper (+/- 10%) 8.1mil

this product has a 1 year shelf life when stored at 72°F and 50% relative humidity

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty