



C1066 13" Dry Edge

2mil Clr PP Indigo TC | crocLock HCW Dry Edge | 40#

This face stock is a transparent, top-coated, BOPP. Its top-coating is suitable for printing on HP digital presses.

facestock

caliper (+/- 10%)	2mil
surface tension	42
MD/CD tensile (k lbs/in)	20/35
MD/CD elongation %	180/55



2-Sided Limited Ooze or 4-Sided No Ooze Dry Edge

an aggressive hot-melt adhesive

for difficult to label surfaces

the MVP at PRI Plus

CrocLock is designed with quick tack properties and excellent on press convertibility.

adhesive

Common Applications

- | | |
|--------------|------------|
| ✚ wood | ✚ plastics |
| ✚ corrugated | ✚ textured |

caliper (+/- 10%)	1.2mil
min application temp (°F)	30
service range (°F)	-40-145
180° peel (PLI)	5.5
RT loop tack (PLI)	6
saft (°F)	140

This is a 40# bleached, super calendered kraft liner. This liner features excellent die cutting and matrix stripping.

liner

caliper (+/- 10%)	2.4mil
-------------------	--------

total caliper (+/- 10%) 5.6mil

this product has a 1 year shelf life when stored at 72°F and 50% relative humidity

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty

www.priplus.com