



CR2SG

2.6mil Gloss Wht PP TC 4"x6" | tire HCW Dry Edge | 40#

This is a white, high gloss, BOPP Film that is top-coated for excellent print performance and ink adhesion. It is print receptive for UV flexo, water flexo, gravure, UV inkjet, hot stamp, and thermal transfer printing methods.

Features and Benefits

- ✦ excellent die-cut performance
- ✦ pearlized look for graphics enhancement
- ✦ great stiffness for efficient dispensability

caliper (+/- 10%)	2.6mil
gloss (45°)	90
Opacity %	90
MD/CD elongation %	150/50
MD/CD tensile (K lbs/in)	13.1/29

facestock



1/8" 4-Sided No Ooze Dry Edge an aggressive hot-melt adhesive for difficult to label surfaces

Tire is designed to maintain adherence on rough surfaces.
Tire has excellent initial tack and flow.

Common Applications

- ✦ tires
- ✦ wood
- ✦ masonry
- ✦ carpet backing
- ✦ horticultural
- ✦ steel yard

caliper (+/- 10%)	3mil
min application temp (°F)	10
service range (°F)	-60—145
180° peel (PLI)	5
RT loop tack (PLI)	6
saft (°F)	160

adhesive

This is a 40# bleached, super calendered kraft liner. This liner features excellent die cutting and matrix stripping.

caliper (+/- 10%)	2.4mil
-------------------	--------

liner

total caliper (+/- 10%) 8mil

this product has a 1 year shelf life when stored at 72°F and 50% relative humidity

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty