



## C1012

### 50# Coated TT | crocLock | 40#

This facestock is designed for pressure sensitive thermal transfer applications with conventional pre-print. The coatings on this grade are optimized for thermal transfer printing, while providing a surface for flexographic preprinting. This grade features a smooth surface and high strength for fast printing and matrix stripping.

#### Features and Benefits

✦ coatings designed for thermal transfer printing	caliper (+/- 10%)	3.1mil
✦ smooth surface for good bar code reproduction	smoothness (5S, PPS)	2.00
✦ smudge resistance for durable bar code image	opacity %	87
✦ high strength for fast matrix stripping	brightness %	85
✦ high brightness and blue-white shade	CD tensile (lbs/in)	17
for good label appearance	MD tear (g)	42

facestock



an aggressive hot-melt adhesive  
for difficult to label surfaces

the MVP at PRI Plus

CrocLock is designed with quick tack properties and excellent on press convertibility.

#### Common Applications

✦ wood	✦ plastics
✦ corrugated	✦ textured

Complies with FDA 21CFR 175.105  
indirect food contact

caliper (+/- 10%)	1mil
min application temp (°F)	30
service range (°F)	-40-145
180° peel (PLI)	5.5
RT loop tack (PLI)	6
saft (°F)	140

adhesive

This is a 40# bleached, super calendered kraft liner. This liner features excellent die cutting and matrix stripping.

caliper (+/- 10%) 2.4mil

liner

total caliper (+/- 10%) 6.5mil

this product has a 1 year shelf life when stored at 72°F and 50% relative humidity

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty

[www.priplus.com](http://www.priplus.com)