



CR2ST

50# Coated TT 4"x6" | tire HCW Dry Edge | 40#

This facestock is designed for pressure sensitive thermal transfer applications with conventional pre-print. The coatings on this grade are optimized for thermal transfer printing, while providing a surface for flexographic preprinting. This grade features a smooth surface and high strength for fast printing and matrix stripping.

Features and Benefits

- ✦ coatings designed for thermal transfer printing
- ✦ smooth surface for good bar code reproduction
- ✦ smudge resistance for durable bar code image
- ✦ high strength for fast matrix stripping
- ✦ high brightness and blue-white shade for good label appearance

caliper (+/- 10%)	3.1mil
smoothness (5S, PPS)	2.00
opacity %	87
brightness %	85
CD tensile (lbs/in)	17
MD tear (g)	42

facestock



1/8" 4-Sided No Ooze Dry Edge an aggressive hot-melt adhesive for difficult to label surfaces

Tire is designed to maintain adherence on rough surfaces.
Tire has excellent initial tack and flow.

Common Applications

- ✦ tires
- ✦ wood
- ✦ masonry
- ✦ carpet backing
- ✦ horticultural
- ✦ steel yard

caliper (+/- 10%)	3mil
min application temp (°F)	10
service range (°F)	-60—145
180° peel (PLI)	5
RT loop tack (PLI)	6
saft (°F)	160

adhesive

This is a 40# bleached, super calendered kraft liner. This liner features excellent die cutting and matrix stripping.

caliper (+/- 10%)	2.4mil
-------------------	--------

liner

total caliper (+/- 10%) 8.5mil

this product has a 1 year shelf life when stored at 72°F and 50% relative humidity

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty