



C1016

3.2mil Matte Wht PE TT | crocLock HCW | 40#

This polyolefin-based, clay-coated film is designed to be compatible with most print methods.

This film provides superior performance where resistance to tear, grease, moisture, and temperature fluctuation is needed. It will die cut and fold easily. It is also compatible with hot stamping and embossing. Outdoor durability will last up to 18 months depending on the climate and exposure. When using for hand held applications, it is recommended to remove the liner from the label in order to reduce pickers curl.

facestock

caliper (+/- 10%) 3.2mil



an aggressive hot-melt adhesive
for difficult to label surfaces

the MVP at PRI Plus

CrocLock is designed with quick tack properties and excellent on press convertibility.

Common Applications

- ✦ wood
- ✦ corrugated
- ✦ plastics
- ✦ textured

caliper (+/- 10%)	1.2mil
min application temp (°F)	30
service range (°F)	-40-145
180° peel (PLI)	5.5
RT loop tack (PLI)	6
saft (°F)	140

adhesive

This is a 40# bleached, super calendered kraft liner. This liner features excellent die cutting and matrix stripping.

caliper (+/- 10%) 2.4mil

liner

total caliper (+/- 10%) 6.8mil

this product has a 1 year shelf life when stored at 72°F and 50% relative humidity

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty

www.priplus.com