



C1096

2.3mil Gloss Wht PP TC | snappLock B | 40#

This is a white, high gloss, BOPP film that is top-coated for flexographic, gravure, silkscreen, and letterpress processes. Features include high opacity, excellent hot/cold moisture resistance, semi-squeeze performance, high stiffness for conversion and automatic dispensing, balanced biaxial orientation for superior, even die cutting enhancing label edge appearance and prolonging die life.

facestock

caliper (+/- 10%)	2.3mil
opacity %	80
MD/CD elongation %	85/110
MD/CD tensile (K lbs/in)	26.1/21.7



an aggressive hot-melt adhesive
for difficult to label surfaces

SnappLock features high initial tack and peel values. It has excellent die cutting capabilities, maximizing press speeds. SnappLock excels on cylindrical applications and smooth, or moderately textured surfaces.

adhesive

Common Applications

- ✦ powder coated
- ✦ stainless steel
- ✦ low surface energy plastics
- ✦ recycled corrugated

caliper (+/- 10%)	1.4mil
min application temp (°F)	40
service range (°F)	-40-190
180° peel (PLI)	7.2
RT loop tack (PLI)	11.3
saft (°F)	160

This is a 40# bleached, super calendered kraft liner. This liner features excellent die cutting and matrix stripping.

liner

caliper (+/- 10%)	2.4mil
-------------------	--------

total caliper (+/- 10%) 6.1mil

this product has a 1 year shelf life when stored at 72°F and 50% relative humidity

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty