**Facestock** 





Rev. No.02.03.03 Date 19JAN24

## C1070 Destructible C1S | snappLock | 40#

This coated-one-side paper is designed for flexographic, thermal transfer, and impact print methods. This product will delaminate easily- showing evidence of tampering. This product is press friendly when compared to most destructible "flaking" film face stocks.

caliper (+/- 10%) 2.7mil opacity % 90



## an aggressive hot-melt adhesive for difficult to label surfaces

SnappLock features high initial tack and peel values. It has excellent die cutting capabilities, maximizing press speeds. SnappLock excels on cylindrical applications and smooth, or moderately textured surfaces.

1mil	caliper (+/- 10%)				
40	application temp (°F)	Common Applications min application temp (		Commo	
-40-190	service range (°F)	urface energy plastics	井 low surfac	powder coated	#
7.2	180° peel (PLI)	cled corrugated	# recycled o	stainless steel	#
11.3	RT loop tack (PLI)				
160	saft (°F)				

This is a 40# bleached, super calendered kraft liner. This liner features excellent die cutting and matrix stripping.

caliper (+/- 10%) 2.4mil

total caliper (+/- 10%) 6.5mil

this product has a 1 year shelf life when stored at 72°F and 50% relative humidity

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty