180



C1015E

60# Semigloss | crocLock-e HCW | 40#

A premium coated semigloss paper that provides excellent printing characteristics using flexo, offset, or letterpress. It is a porous material that allows ink to absorb.

Features and Benefits

- Designed for high end labels
- Sharper resolution allows photo prints to pop
- # greater contrast between light and dark shades
- enhanced blue-white shade
- high strength for high speed matrix stripping.

	DOUGH BUILDINGS	
aliper	(+/- 10%)	3.1mil

gloss 70

opacity % 87.5

brightness % 89



an aggressive hot-melt adhesive for difficult to label surfaces

CrocLock-e is an enhanced formula of our crocLock adhesive. We've sacrificed just a touch of the strong initial tack of crocLock to provide a higher shear adhesive failure temperature, meaning crocLock-e holds more reliably at a higher temperature service range.

Common Applications

- + extended shipping + warehouse storage
- industrial containers

1.2mil	caliper (+/- 10%)	
0	min application temp (°F)	
-20-180	service range (°F)	
6.2	180° peel (PLI)	
6.8	RT loop tack (PLI)	

SAFT (°F)

This is a 40# bleached, super calendered kraft liner. This liner features excellent die cutting and matrix stripping.

caliper (+/- 10%) 2.4mil

total caliper (+/- 10%) 6.7mil

this product has a 1 year shelf life when stored at 72°F and 50% relative humidity

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty