



# C1111E

## 43# Coated TT | crocLock-e HCW | 40#

This facestock is designed for pressure sensitive thermal transfer applications with conventional pre-print. The coatings on this grade are optimized for thermal transfer printing, while providing a surface for flexographic preprinting. This grade features a smooth surface and high strength for fast printing and matrix stripping.

### Features and Benefits

- ✦ coatings designed for thermal transfer printing
- ✦ smooth surface for good bar code reproduction
- ✦ smudge resistance for durable bar code image
- ✦ high strength for fast matrix stripping
- ✦ high brightness and blue-white shade for good label appearance

caliper (+/- 10%)	1.2mil
smoothness (5S, PPS)	2.00
opacity %	87
brightness %	85
CD tensile (lbs/in)	17
MD tear (g)	42

facestock



### an aggressive hot-melt adhesive for difficult to label surfaces

CrocLock-e is an enhanced formula of our crocLock adhesive. We've sacrificed just a touch of the strong initial tack of crocLock to provide a higher shear adhesive failure temperature, meaning crocLock-e holds more reliably at a higher temperature service range.

### Common Applications

- ✦ extended shipping
- ✦ warehouse storage
- ✦ industrial containers

caliper (+/- 10%)	1.2mil
min application temp (°F)	0
service range (°F)	-20—180
180° peel (PLI)	6.2
RT loop tack (PLI)	6.8
SAFT (°F)	180

adhesive

This is a 40# bleached, super calendered kraft liner. This liner features excellent die cutting and matrix stripping.

caliper (+/- 10%)	2.4mil
-------------------	--------

liner

total caliper (+/- 10%) 4.8mil

this product has a 1 year shelf life when stored at 72°F and 50% relative humidity

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty