



C1205

2mil Clear PP TC | crocLock-e HCW | 40#

This is a transparent, top-coated, BOPP film.

facestock

caliper (+/- 10%)	2mil
surface tension	42
MD/CD elongation %	180/55
MD/CD tensile (k lbs/in ²)	20/35



an aggressive hot-melt adhesive
for difficult to label surfaces

CrocLock-e is an enhanced formula of our crocLock adhesive. We've sacrificed just a touch of the strong initial tack of crocLock to provide a higher shear adhesive failure temperature, meaning crocLock-e holds more reliably at a higher temperature service range.

Common Applications

- ✦ extended shipping ✦ warehouse storage
- ✦ industrial containers

caliper (+/- 10%)	1.4mil
min application temp (°F)	0
service range (°F)	-20—180
180° peel (PLI)	6.2
RT loop tack (PLI)	6.8
SAFT (°F)	180

adhesive

This is a 40# bleached, super calendered kraft liner. This liner features excellent die cutting and matrix stripping.

caliper (+/- 10%)	2.4mil
-------------------	--------

liner

total caliper (+/- 10%) 5.8mil

this product has a 1 year shelf life when stored at 72°F and 50% relative humidity

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty