1.8mil



C1153

50# TT | timberTack + | 40#

This facestock is designed for pressure sensitive thermal transfer applications with conventional pre-print. The coatings on this grade are optimized for thermal transfer printing, while providing a surface for flexographic preprinting. This grade features a smooth surface and high strength for fast printing and matrix stripping.

Features and Benefits

coatings designed for thermal transfer printing	caliper (+/- 10%)	3.1mil
smooth surface for good bar code reproduction	smoothness (5S, PPS)	2.00
smudge resistance for durable bar code image	opacity %	87
high strength for fast matrix stripping	brightness %	85
💠 high brightness and blue-white shade	CD tensile (lbs/in)	17
for good label appearance	MD tear (g)	42



an aggressive hot-melt adhesive for difficult to label surfaces

TimberTack is designed as a soft adhesive to create maximum contact with the application surface. TimberTack is an extra aggressive adhesive.

		min application temp (°F)	10
⊹ wood	↓ burlap	service range (°F)	-60-145
carpet backing	→ HDPE	180° peel (PLI)	5
∔ livestock	recycled corrugated	RT loop tack (PLI)	6
	packaging	Saft (°F)	160

This is a 40# bleached, super calendered kraft liner. This liner features excellent die cutting and matrix stripping.

caliper (+/- 10%) 2.4mil

total caliper (+/- 10%) 7.3mil

caliper (+/- 10%)

this product has a 1 year shelf life when stored at 72°F and 50% relative humidity

Published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty