label constructions



Product Data Sheet: CR2SG-F

2.6mil Gloss Wht PP TC 4"x6" | foamLoch HCW Dry Edge | 40#

Rev. No. 04.01.01 | Date 29APR24

This is a white, high gloss, BOPP film that is top-coated for excellent print performance and ink adhesion.

Our CR2SG-F is a roll of 4 inch by 6 inch die-cut labels.

excellent die-cut performance pearlized look for graphic enhancement great stiffness for efficient dispensability

caliper (+/- 10%)	2.6mil
gloss (45°)	90
Opacity %	90
MD/CD elongation %	150/50
MD/CD tensile (K lbs/in)	13.1/29

print methods: Flexo, UV Flexo, water Flexo, UV inkjet, thermal transfer, gravure, hot stamp

an aggressive hot-melt adhesive for foam

FoamLoch is a highly conformable, high flow aggressive adhesive. This allows for ultra surface contact making this adhesive a great choice for rough, uneven, and porous surfaces- predominately on open cell structure foams.. FoamLoch is perfect for both high-density, firm foam applications as well as low-density, soft foam applications.

very high flow properties ultra soft adhesive maximum surface contact good initial tack excellent cold resistance minor heat resistance



caliper (+/- 10%) 3mil min app temp (°F) 0 service range (°F) -60—130 180° peel (PLI) 7.5 RT loop tack (PLI) 5.5 SAFT (°F) 140



1/8" 4-sided Dry Edge

This no ooze barrier will ensure the extra adhesive won't gunk up your printer.









This is a 40# bleached, super calendered kraft liner.

This liner features excellent die cutting and matrix stripping.

caliper (+/- 10%) 2.4mil

total caliper (+/- 10%) 8mil

this product has a 1 year shelf life when stored at 72°F and 50% relative humidity
estimated roll weight may vary substantially: width (in) x length (in) x 0.0324
published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty

^{*} minimum temperature and service temperature range are projections based off ongoing testing