

Product Data Sheet: CR2SG-TS

2.6mil Gloss Wht PP TC 4"x6" | tire-s HCW Dry Edge | 40#

Rev. No. 04.01.01 | Date 30APR24

This is a white, high gloss, BOPP film that is top-coated for excellent print performance and ink adhesion.
Our CR2SG-TS is a roll of 4 inch by 6 inch die-cut labels.

excellent die-cut performance
pearlized look for graphic enhancement
great stiffness for efficient dispensability

caliper (+/- 10%)	2.6mil
gloss (45°)	90
Opacity %	90
MD/CD elongation %	150/50
MD/CD tensile (K lbs/in)	13.1/29

print methods: Flexo, UV Flexo, water Flexo, UV inkjet, thermal transfer, gravure, hot stamp

facestock

an aggressive hot-melt adhesive for tires

Tire-s is a versatile pressure-sensitive adhesive designed to conform to both tire walls and tire tread.

extra surface contact
very high flow properties
ultra soft adhesive
maximum surface contact
good initial tack / smooth release
excellent cold / minor heat resistance



caliper (+/- 10%)	3mil
min app temp (°F)	0
service range (°F)	-60—130
180° peel (PLI)	7.5
RT loop tack (PLI)	5.5
SAFT (°F)	140

Dry Edge
series

1/8" 4-sided Dry Edge

This no ooze barrier will ensure the extra adhesive won't gunk up your printer.



* minimum temperature and service temperature range are projections based off ongoing testing

adhesive

This is a 40# bleached, super calendered kraft liner.
This liner features excellent die cutting and matrix stripping.

caliper (+/- 10%)	2.4mil
-------------------	--------

total caliper (+/- 10%) 8mil

this product has a 1 year shelf life when stored at 72°F and 50% relative humidity
estimated roll weight may vary substantially: width (in) x length (in) x 0.0324
published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty

liner