label constructions that stick to the stick



## Product Data Sheet: CR2SG

## 2.6mil Gloss Wht PP TC 4"x6" | tire HCW Dry Edge | 40#

Rev. No. 04.01.01 | Date 30APR24

This is a white, high gloss, BOPP film that is top-coated for excellent print performance and ink adhesion.

Our CR2SG is a roll of 4 inch by 6 inch die-cut labels.

excellent die-cut performance pearlized look for graphic enhancement great stiffness for efficient dispensability

caliper (+/- 10%)	2.6mil
gloss (45°)	90
Opacity %	90
MD/CD elongation %	150/50
MD/CD tensile (K lbs/in)	13.1/29

print methods: flexo, UV flexo, water flexo, UV inkjet, thermal transfer, gravure, hot stamp

## an aggressive hot-melt adhesive for tires

Tire is a versatile pressure-sensitive adhesive designed to conform to both tire walls and tire tread.

extra aggressive high flow properties soft adhesive high surface contact excellent initial tack / bitey release great cold / moderate heat resistance



caliper (+/- 10%) 3mil min app temp (°F) 10 service range (°F) -60—145 180° peel (PLI) 5 RT loop tack (PLI) 6 SAFT (°F) 160



1/8" 4-sided Dry Edge
This no ooze barrier will ensure the extra adhesive won't gunk up your printer.



This is a 40# bleached, super calendered kraft liner.

This liner features excellent die cutting and matrix stripping.

caliper (+/- 10%) 2.4mil

total caliper (+/- 10%) 8mil

this product has a 1 year shelf life when stored at 72°F and 50% relative humidity
estimated roll weight may vary substantially: width (in) x length (in) x 0.0324
published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty