

Product Data Sheet: CR2SM-F

3mil Matte Wht PP TC 4"x6" | foamLoch HCW Dry Edge | 40#

Rev. No. 04.01.01 | Date 29APR24

This a matte white, mineral-filled, BOPP film.
Our CR2SM-F is a roll of 4 inch by 6 inch die-cut labels.

matte, print receptive coating
good strength and durability

caliper (+/- 10%) 3mil

print methods: thermal transfer

facestock

an aggressive hot-melt adhesive for foam

FoamLoch is a highly conformable, high flow aggressive adhesive. This allows for ultra surface contact making this adhesive a great choice for rough, uneven, and porous surfaces- predominately on open cell structure foams. FoamLoch is perfect for both high-density, firm foam applications as well as low-density, soft foam applications.

very high flow properties
ultra soft adhesive
maximum surface contact
good initial tack
excellent cold resistance
minor heat resistance



caliper (+/- 10%) 3mil
min app temp (°F) 0
service range (°F) -60—130
180° peel (PLI) 7.5
RT loop tack (PLI) 5.5
SAFT (°F) 140

Dry Edge
series

1/8" 4-sided Dry Edge

This no ooze barrier will ensure the extra adhesive won't gunk up your printer.

* minimum temperature and service temperature range are projections based off ongoing testing



adhesive

This is a 40# bleached, super calendered kraft liner.
This liner features excellent die cutting and matrix stripping.

caliper (+/- 10%) 2.4mil

total caliper (+/- 10%) 8.4mil

this product has a 1 year shelf life when stored at 72°F and 50% relative humidity
estimated roll weight may vary substantially: width (in) x length (in) x 0.0324
published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty

liner