

Product Data Sheet: CR2ST

50# Coated TT 4"x6" | tire HCW Dry Edge | 40#

Rev. No. 04.01.01 | Date 30APR24

This is a 50# coated paper face stock. The coating is optimized for for thermal transfer printing on applications with conventional pre-printing. Our CR2ST is a roll of 4 inch by 6 inch die-cut labels.

smooth surface for good bar code reproduction
smudge resistance for durable bar code image
high strength for fast matrix stripping
high brightness and blue-white shade
for enhanced appearance

caliper (+/- 10%)	3.1mil
smoothness (5S, PPS)	2.00
opacity %	87
brightness %	85
CD tensile (lbs/in)	17
MD tear (g)	42

print methods: thermal transfer

facestock

an aggressive hot-melt adhesive for tires

Tire is a versatile pressure-sensitive adhesive designed to conform to both tire walls and tire tread.

extra aggressive
high flow properties
soft adhesive
high surface contact
excellent initial tack / bitey release
great cold / moderate heat resistance



Dry Edge
series

1/8" 4-sided Dry Edge

This no ooze barrier will ensure the extra adhesive won't gunk up your printer.



caliper (+/- 10%)	3mil
min app temp (°F)	10
service range (°F)	-60—145
180° peel (PLI)	5
RT loop tack (PLI)	6
SAFT (°F)	160

adhesive

This is a 40# bleached, super calendered kraft liner.
This liner features excellent die cutting and matrix stripping.

caliper (+/- 10%)	2.4mil
-------------------	--------

total caliper (+/- 10%) 8.5mil

this product has a 1 year shelf life when stored at 72°F and 50% relative humidity
estimated roll weight may vary substantially: width (in) x length (in) x 0.0324
published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty

liner