

Product Data Sheet: C1310

2.6mil Gloss Wht PP TC | ap2 C | 50#

Rev. No. 04.01.02 | Date 27May25

This product features a white, high gloss, BOPP film that is top-coated for excellent print performance and ink adhesion.

excellent die-cut performance
pearlized look for graphics enhancement
great stiffness for efficient dispensability

caliper (+/- 10%)	2.6mil
gloss (45°)	90
opacity %	90
MD/CD elongation %	150/50
MD/CD tensile (k lbs/in)	13.1/29

print methods: UV flexo, water flexo, gravure, UV inkjet, hot stamp, thermal transfer

facestock

an aggressive hot-melt rubber adhesive for cylindrical applications

Ap1 tackles varied surfaces with confidence and precision. It packs a surprisingly aggressive bite, making it the perfect entry point to the world of aggressive adhesives for general-purpose labeling.

- Surface versatility: bites onto a wide range of surfaces, providing a lot of labeling flexibility.
- Aggressive affordability: delivers serious sticking power at a friendly price-point.

alternative general purpose
considerable tack
considerable peel
reliable temperature resistance



caliper (+/- 10%)	2.4mil
min app temp (°F)	10
service range (°F)	-20—120
180° peel (PLI)	5.7
RT loop tack (PLI)	8.2
SAFT (°F)	147

adhesive



This is a 50# bleached, super calendered kraft liner.
This liner features excellent die cutting and matrix stripping.

caliper (+/- 10%)	3.1mil
-------------------	--------

liner

total caliper (+/- 10%) 8.1mil

this product has a 1 year shelf life when stored at 72°F and 50% relative humidity
published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty