

Product Data Sheet: C1050

3.2mil Matte Wht PE | frzBite | 40#

Rev. No. 04.01.01 | Date 22OCT24

3.2mil Matte Wht PE is a clay-coated two side, highly cavitated & filled,
simultaneous biaxial orientated HDPE film.

* to prevent pickers curl, remove the liner from the label

• superior tear resistance	caliper (+/- 10%)	3.2mil
• great performance with exposure to grease, moisture, and temperature fluctuation	opacity (%)	90
• easy to die-cut and fold	gloss (%)	11
• compatible with hot stamping & embossing	MD/CD elongation (%)	125/130
• up to 18 month outdoor durability	MD/CD tear strength (lbs/in)	570/650
	stiffness (mg)	35

print methods: thermal transfer, flexographic, gravure, UV offset

facestock

an aggressive hot-melt rubber adhesive for cold temperature

Looking for an adhesive that can withstand the cold? Then you need frzBite! FrzBite aggressive adhesive is designed to perform well in cold temperature environments, making it perfect for food packaging applications. With its superior condensation resistance, frzBite is the ideal choice for any project where reliability in low temperatures is key.

high cold resistance
performance through condensation
low application temperature
high surface versatility



caliper (+/- 10%)	1.4mil
min app temp (°F)	-10
service range (°F)	-40—140
180° peel (PLI)	5.9
RT loop tack (PLI)	5.6
SAFT (°F)	150

adhesive



This is a 40# bleached, super calendered kraft liner.
This liner features excellent die cutting and matrix stripping.

caliper (+/- 10%) 2.4mil

total caliper (+/- 10%) 7mil

this product has a 1 year shelf life when stored at 72°F and 50% relative humidity
published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty

liner