

## Product Data Sheet: C1110

### 3.2mil Matte Wht PE | crocLock B | 40#

Rev. No. 04.01.01 | Date 03JUN25

3.2mil Matte Wht PE is a clay-coated two side, highly cavitated & filled, simultaneous biaxial orientated HDPE film.

\* to prevent pickers curl, remove the liner from the label

• superior tear resistance	caliper (+/- 10%)	3.2mil
• great performance with exposure to grease, moisture, and temperature fluctuation	opacity (%)	90
	gloss (%)	11
• easy to die-cut and fold	MD/CD elongation (%)	125/130
• compatible with hot stamping & embossing	MD/CD tear strength (lbs/in)	570/650
• up to 18 month outdoor durability	stiffness (mg)	35

print methods: thermal transfer, flexographic, gravure, UV offset

facestock

### an aggressive hot-melt rubber adhesive for packaging

CrocLock's aggressive tack bites ahold of most surfaces, but it really shines with everyday packaging jobs. Plus, its excellent on-press convertibility keeps your production lines humming. When it comes to boxes, bottles, and shrink wrap, crocLock is the dependable choice that gets the job done.

- Quick-Tack Properties: label in a flash with instant adhesion.
- Dust and Debris Resistance: Conquers dust, dirt, and debris for reliable hold in any environment.

high initial tack  
moderate temperature resistance  
great adhesion on textured surfaces



caliper (+/- 10%)	1.5mil
min app temp (°F)	30
service range (°F)	-40—145
180° peel (PLI)	5.5
RT loop tack (PLI)	6
SAFT (°F)	140

adhesive



This is a 40# bleached, super calendered kraft liner.  
This liner features excellent die cutting and matrix stripping.

caliper (+/- 10%) 2.4mil

total caliper (+/- 10%) 7.1mil

this product has a 1 year shelf life when stored at 72°F and 50% relative humidity  
published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty

liner