

Product Data Sheet: C1117

3.2mil Matte Wht PE | timberTack C | 40#

Rev. No. 04.01.01 | Date 02JUN25

3.2mil Matte Wht PE is a clay-coated two side, highly cavitated & filled, simultaneous biaxial orientated HDPE film.

* to prevent pickers curl, remove the liner from the label

• superior tear resistance	caliper (+/- 10%)	3.2mil
• great performance with exposure to grease, moisture, and temperature fluctuation	opacity (%)	90
• easy to die-cut and fold	gloss (%)	11
• compatible with hot stamping & embossing	MD/CD elongation (%)	125/130
• up to 18 month outdoor durability	MD/CD tear strength (lbs/in)	570/650
	stiffness (mg)	35

print methods: thermal transfer, flexographic, gravure, UV offset

facestock

an aggressive rubber adhesive for wood & horticulture

TimberTack's secret weapon is its surprisingly soft formula. This clever extra aggressive adhesive seeps into every pore and crevice, forming an unbreakable bond with even the roughest, most textured materials. Unlike stiff adhesives that bridge over uneven surfaces, timberTack's soft formula allows it to fill the gaps to create a larger bonding surface for ultimate strength. Nature Lover's Rejoice, timberTack's solvent-free formula is an eco-friendly choice for a wide range of horticultural applications.

extra aggressive
moderately soft adhesive
high surface contact
excellent initial tack
high flow properties
great cold resistance
moderate heat resistance



caliper (+/- 10%)	2.2mil
min app temp (°F)	10
service range (°F)	-60—145
180° peel (PLI)	5
RT loop tack (PLI)	6
SAFT (°F)	160

adhesive



This is a 40# bleached, super calendered kraft liner.
This liner features excellent die cutting and matrix stripping.

caliper (+/- 10%)	2.4mil
-------------------	--------

total caliper (+/- 10%) 7.8mil

this product has a 1 year shelf life when stored at 72°F and 50% relative humidity
published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty

liner