

Product Data Sheet: C1111E

43# Coated TT | crocLock-e HCW | 40#

Rev. No. 04.01.01 | Date 21OCT25

The 43# Coated TT is designed for pressure sensitive thermal transfer applications with conventional preprint.

- smooth surface for good bar code reproduction
- smudge resistance for durable bar code image
- high strength for fast matrix stripping
- high brightness and blue-white shade for good label appearance

caliper (+/- 10%)	2.9mil
smoothness (5S, PPS)	2.00
opacity (%)	87
brightness (%)	85
CD tensile (lbs/in)	17
MD tear (g)	42

print methods: thermal transfer, flexographic preprint

facestock

an aggressive hot-melt rubber adhesive for packaging

CrocLock-e's aggressive tack bites ahold of most surfaces, but it really shines with packaging jobs. Plus, its excellent on-press convertibility keeps your production lines humming. When it comes to boxes, bottles, and shrink wrap, crocLock-e is the dependable choice that gets the job done.

- Quick-Tack Properties: label in a flash with instant adhesion.
- Dust and Debris Resistance: Conquers dust, dirt, and debris for reliable hold in any environment.

- moderate initial tack
- high temperature resistance
- less ooze
- good adhesion on textured surfaces



caliper (+/- 10%)	0.8mil
min app temp (°F)	0
service range (°F)	-20—180
180° peel (PLI)	6.2
RT loop tack (PLI)	6.8
SAFT (°F)	180

adhesive



This is a 40# bleached, super calendered kraft liner.
This liner features excellent die cutting and matrix stripping.

caliper (+/- 10%)	2.4mil
-------------------	--------

total caliper (+/- 10%) 6.1mil

this product has a 1 year shelf life when stored at 72°F and 50% relative humidity
published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty

liner