

Product Data Sheet: C1280

40# ER | snappLock transfer adhesive | 40# TR

Rev. No. 04.01.01 | Date 05MAY26

This is a 40# easy release
bleached, super calendered kraft liner.
This liner features excellent die cutting and matrix stripping.

caliper (+/- 10%) 2.4mil

liner

an aggressive hot-melt adhesive for cylindrical applications

SnappLock is a high-performance adhesive boasting exceptional versatility. It has a high initial tack & peel, conquering diverse substrates, including cylindrical applications. Experience increased production efficiency thanks to snappLock's superior die-cutting properties, ensuring consistent, clean cuts.

high performance
superior tack
high surface adhesion versatility
excellent die-cutting
high temperature resistance



caliper (+/- 10%) 1mil
min app temp (°F) 40
service range (°F) -40—190
180° peel (PLI) 7.2
RT loop tack (PLI) 11.3
SAFT (°F) 160

adhesive



This is a 40# tight release
bleached, super calendered kraft liner.
This liner features excellent die cutting and matrix stripping.

caliper (+/- 10%) 2.4mil

liner

total caliper (+/- 10%) 5.8mil

this product has a 1 year shelf life when stored at 72°F and 50% relative humidity
published data is based on testing and believed to be reliable but does not constitute a guarantee or warranty